



ENERGREEN[®] *America*
Professional Machines



CONVEYORHEAD



TECHNICAL DATA SHEET CUTTING HEAD WITH CONVEYOR BELT 47" / 59"

CONVEYORHEAD

ENGINE PLUMBER
FOR CONVEYOR BELT

FRAME IN HIGH STRENGTH STEEL

JACK
OPENING FOR
CONVEYOR BELT

CONVEYOR HEAD

SUPPORT ROLLER

FIXED SIDE SKIDS

4 TYPES OF ROTORS



ARTICULATED
BLADE ROTOR



MULTI
Y-BLADES
ROTOR



HALF-TURN
BLADE ROTOR



FORESTRY
HAMMERS
ROTOR

CONVEYOR HEAD is a cutting head whose frame is built in Domex steel. It rises from the experience of the project New Speed, well-established on the experience acquired over the years, Conveyor head differs from a traditional classic cutting head in the larger dimension of the output channel of residual cut material, creating the opportunity to install a conveyor belt (hydraulically operated) to avoid that residual vegetation falls immediately behind the cutting head.

It is suitable for picking up and directing cut material out of the work zone. It is recommended, in particular, for the maintenance of river areas (canals and embankments, etc.) because it is possible to cut the vegetation and throw cut materials off (through the conveyor belt) at the same time, just up to 79" away from the point of cutting. Conveyor head is particularly appropriated in those areas where cut grass does not have to fall into rivers and ditches' water, permitting a better maintenance of water pumps or other related watercourses' plants. The hydraulically operated conveyor belt can rotate in both senses, allowing working continuously on both sides of the ditch and the possibility to decide where to direct cut material.



TECHNICAL DATA

	CONVEYOR HEAD 47	CONVEYOR HEAD 59
Working width	47"	55"
Maximum width	54"	66"
Depth	46"	46"
Height	26"	26"
Cutting diameter	0.79"	0.79"
Weight	1014 lb	1146 lb