



Multihog



CX MK II

Features & Technical Specification

CX MK II

HIGHLIGHTS



ULTRA-CLEAN ENGINE

75 hp Deutz engine, meeting Stage V/Tier 4 final emissions regulations without requiring Ad Blue.



EASY DOUBLE ACCESS

Entrance point has been re-designed for easier entry and exit, and both doors are fully functional for access.



ARMREST & CONTROLS

Controls are built into a large and ergonomic armrest, with fingertip paddles for comfortable operation.



UNPARALLELED CARRYING CAPACITY

The CX MK II still comes with an incredible 3500kg-4000kg (7716lb-8818lb) gross vehicle weight.



LARGE OPERATOR CABIN

The new cabin is much bigger, and has a more spacious and comfortable feel for operators working long shifts.



SUPERB HEATING & A/C

Heating and air con functions have been supercharged to deliver even more effective airflow in the cabin.



ON-BOARD DIAGNOSTICS

Large in-cabin screen displays the machine's critical diagnostics for super simple remote troubleshooting.



LIFT & AXLE CAPACITY

Lift capacity (1200kg/2646lb) and axle capacity (2500kg/5512lb) are great for heavy attachments.

THE CX MK II

IS COMPATIBLE WITH YOUR EXISTING ATTACHMENTS!




One Machine - One Operator - Endless Applications



CX MK II SPECIFICATION

- ◆ Engine: Deutz, 75 hp (2.2 litre)
- ◆ Emissions class: Stage V (EU), Tier 4 Final (USA/CA)
- ◆ Length: 3860 mm (152 in)
- ◆ Width: 1200 - 1610 mm (47 - 63 in)
- ◆ Height: 2235 mm (88 in), tyre dependent
- ◆ Wheelbase: 1900 mm (75 in)
- ◆ Unladen weight: 2200 - 2500 kg (4850 - 5511 lb)
- ◆ Axle capacity, front, tyre dependent: 2500 kg (5511 lb)
- ◆ Axle capacity, rear, tyre dependent: 2500 kg (5511 lb)
- ◆ Gross vehicle weight: 3500 - 4000 kg (7716 - 8818 lb)
- ◆ Outer turning radius: 2990 - 3190 mm (118 - 126 in)
- ◆ Maximum speed: 40 km/h (25 mph)
- ◆ Hydraulics: Load-sensing PTO hydraulics front & rear, with optional front mechanical PTO
- ◆ Flow: Hydraulic flow up to 100 litres (26.4 gal)
- ◆ Operating pressure: Up to 220 bar (3190 psi)

Your local authorised dealer is:



- 🏠 Multihog Global Headquarters,
Finnabair Business Park, Dundalk, Co. Louth, Ireland.
- ✉ info@multihog.com
- ☎ +353 42 9386738 / 443 852 1842 (US/CA)
- 🌐 www.multihog.com



Due to our policy of continuous improvement, reasonable alterations & changes to the specifications of our products may take place subsequent to the publication of this brochure & we reserve the right to make such changes without prior notice.

