



# Multihog<sup>®</sup>

One Machine - One Driver - Endless Applications



### Gully & Sewer Cleaner

#### MGC 900

- Mounted on the CX tractor for the removal and transportation of liquid waste & sludge, the gully cleaner is ideal for accessing narrow or confined spaces to clean sewers, gullies and drains
- 900 litre (238 gal) tank, comprising a 600 litre/158 gal sludge chamber with a 300 litre/79 gal water chamber, emptied via the Multihog's hydraulic tipping function
- Can be operated without the boom arm, keeping the vehicle height at 2000 mm (6.5 ft) which allows it to operate in multi-storey car parks and similar
- Boom arm can be hydraulically raised 40° (vertically) and can be pivoted 270° (manually)
- Integrated water filter means the tank can be filled from open water bodies using the 3" suction connection - both sludge and water levels are visible using the eyeglass on the cleaner
- The sludge vacuum system is powerful, operating at 750 m<sup>3</sup>/h (440 cfm). A high pressure piston pump operates at 50 l/min (12.3 gal/min) and 150 bar (2900 psi).
- 10 metre (1/2") hose reel mounted on rear door and there is an emergency button on the rear of the vehicle
- A mechanical unloader valve for continuous pressure regulation protects the jetting system against overload and the cleaner also features a rear view camera system with 7" in-cabin monitor

*Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.*

