



Multihog[®]

One Machine - One Driver - Endless Applications



Rotary Mower

MMM 8400

- Rotary mower ideal for mowing parklands, military bases, airfields & racecourses
- View from the Multihog during mowing is 100% clear, with no obstruction
- The mower is gear-driven
- Internal roller bearings give total protection against moisture and soil
- The mower is available in a range of sizes, with overall widths from 2 - 4.2 metres (6'6" - 14') approx.
- Working width ranges from 1.9 - 4.1 metres (6'3" - 13'5"), depending on mower model
- Cutting height is adjustable between 10 - 150 mm (0.4" - 6")
- Mowing rates of between 5.3 and 11.5 acres per hour at a speed of 7mph (depending on conditions)
- 6 ply tyre on the castor wheels for added durability
- Mowers are available as both rigid and winged versions

Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.



Rotary Mower MRM TH2500

- Front-mounted, hydraulically driven winged rotary mower for our CX tractor range
- Features hydraulically adjustable mowing height and six heavy duty castor wheels
- Mower wings can be hydraulically lifted, and have an auto stop function when lifted more than 30°
- Hydraulic tilt-up as standard for easy maintenance and cleaning
- Working width of 2.5 metres (8 ft)
- Transport width of 1.75 metres (5.7 ft)
- Cutting height adjustable between 20 - 80 mm (0.8 - 3.1 in)
- Fully operated via joystick from within the Multihog cabin, ensuring the driver stays warm & dry

Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.

